55 Hilton Street, Easton PA 18042
(269) 488-4000
www.alumilite.com

TECHNICAL DATA SHEET

Fiber-Lok Non-Skid Backing

Alumilite Fiber-Lok is a non-skid textile backing designed to keep area rugs, mats, and runners securely in place. Perfect for various flooring types and fabrics, this easy-to-apply solution provides long-lasting results, preventing slips and enhancing safety in your home.

PRODUCT FEATURES

- **Fabric and Floor Safe:** Fiber-Lok is gentle on all surfaces, including rugs and floors, ensuring no damage during use.
- **Washable:** Fiber-Lok is machine washable and dryable, maintaining its non-skid properties even after multiple washes.
- **Easy Application:** Simply brush a thin, even coat on the backside of your rug or mat, and it dries clear for a seamless, non-intrusive finish.
- **Grips on Any Surface:** Effective on tile, laminate, hardwood, and more, providing a secure hold for rugs in various environments.
- **Non-Slip Protection:** Prevents rugs from slipping, enhancing safety by keeping mats, runners, and area rugs firmly in place.
- **No Staining:** Dries crystal clear without staining or leaving residue, making it safe for use on any flooring.
- **Latex-Free:** Contains natural rubber latex, making it a safe option for most users; however, individuals with latex allergies should avoid use.

INSTRUCTIONS FOR USE

1. Lay the rug or mat flat on a clean surface.
2. Brush a thin, even layer of Fiber-Lok onto the backside of the rug.
3. Allow the product to dry completely (typically 30-40 minutes, depending on conditions).
4. Repeat for additional layers as needed for extra grip.

- **Drying Time:** Allow 300-40 minutes for the backing to dry to the touch, with complete curing occurring after 24 hours.
- **Coverage:** A 16oz bottle covers approximately 15 sq. ft.

APPLICATIONS

- **Rugs & Mats**: Ideal for keeping area rugs, floor mats, and runners securely in place, preventing dangerous slips.
- **Home & Office**: Use on various floor types, including tile, laminate, hardwood, and carpeted surfaces, for extra safety.

- **Fabric & Textile Projects**: Can be applied to the back of rugs and fabric items to create non-slip effects.

SPECIFICATIONS

• **Composition**: Natural rubber latex-based anti-skid formula
• **Drying Time**: 30-40 minutes (depending on application thickness and conditions)
• **Coverage**: One 16 oz bottle covers approximately 15 sq. ft.
• **Staining**: Dries clear and will not stain or leave a residue.
• **Suitable for**: Tile, laminate, hardwood floors, and various fabrics.

BEFORE YOU BEGIN

Epoxy Work Environment: The ideal working temperature is around 65-75°F in a clean, dry, dust-free environment. Avoid working in high humidity.

Materials: Be prepared with all necessary materials and tools before beginning your project.

- Mixing tools
- Clean brush or applicator for even distribution of the product
- Gloves and PPE

CLEAN UP & DISPOSAL

• **Clean-up**: Clean brushes and applicators with warm, soapy water immediately after use.
• **Disposal**: Dispose of any unused product and containers according to local, state, and federal regulations.

SAFETY

Safety: Before use, thoroughly read Safety Data Sheets and product labels. Follow safety precautions and directions.

- Wear gloves
- Safety glasses
- Protect clothing with a work smock or other outer garment
- For cleaning surfaces, containers – use Acetone, rubbing alcohol or nail polish remover
- When stored separately, epoxy & hardener have long shelf lives – store in a cool dry area in tightly sealed containers

DISCLAIMER: The information contained herein is considered accurate; however, Alumilite makes no warranty regarding its accuracy. The user must determine the suitability of the product for the intended use and accepts all risk and liability associated with that use.